




Push Button and Power Supply (prices for top quality and popular)				
AB-400 Door Remote Control, Wireless for Lock Control 		Input: 12VDC (24VDC by Optional), 8mA Optional: AB-400A transmitter Contact Output: NO/NC/COM Transmitting Freq: 433.92MHZ Transmitting Distance: ≥ 70 m(open area) Finished for Shell: Plastic, Abrasion Resistant, Capable of to 30 Transmitter		 Economic Remote Control
AB-800 Remote Control for Both Parking and Door, Wireless for Lock Control		Support Both Parking and Door simultaneously; Input: 12VDC (24VDC by Optional), 8mA; Optional: AB-400A transmitter; Contact Output: NO/NC/COM; Transmitting Freq: 433.92MHZ; Transmitting Distance: ≥ 50 m(open area); Capable of to 30 Transmitter; Study key for set up		 Economic Remote Control
AB-400RC Remote Control with White Button		Size: 60Lx42Wx28H(mm) Input: 12VDC;Current: ≤ 12 mA Transmitting Distance: 50m(in open area) Shell: Plastic, Abrasion Resistant Contact Output: NO\NC\COM Transmitting Freq:433.92MHZ		
K1-1 (Oblong) K2-2 (Square) Infrared Push Button Optional back box 		Infrared Exit Button 115Lx70Wx29H(mm) 86Lx86Wx29H(mm) 12-28V,3A NO\NC\COM		 +
K2(Oblong) Infrared Push Button Optional back box		Non touch Exit Sensor with Remote Key(Diffused Detection) NO NC COM relay output Size: 115Lx70W(mm)		

AB-802 AB-800B-P (Plastic Back Box)		Plastic Exit Button NO\COM 86*86*20mm			optional + 
AB-800A (Oblong) AB-800B (Square) Optional Back Box		Aluminium Alloy Exit Button NO\NC\COM AB-800A: 86Lx50Wx20H(mm) AB-800B: 86Lx86Wx20H(mm)			optional + 
AB-801A (Oblong) AB-801B (Square) Optional Back Box		Stainless Steel Exit Button AB-801A: NO\COM; 91*28*20mm AB-801B: NO\NC\COM; 86*86*20mm			
AB-805 Alloy Exit Button with Integrated Back Box 		Alloy Plate, Steel Button NO\COM 83*32*25mm			
AB-814B(LED) AB-814C(LED) (with Luminous) Optional Back Box		AB-814B(LED) (Oblong) 86Lx50Wx31H(mm) AB-814C(LED) (Square) 86Lx86Wx31H(mm) Stainless Steel Button, with Night Luminous Current Rating: 3A@36VDC Max Output Contact: NO\NC\COM			optional + 
AB-814D(Oblong) Super Big Optional Back Box		114Lx70Wx31H(mm) Super Big Stainless steel Panel, Steel Button 3A@36VDC Max NO\COM 500000 tested Stainless steel Panel, Wire Drawing Finished			optional LED Night Luminous 
EL-820B/C(LED) Piezoelectric Luminous Exit Button Waterproof Level IP-68 Optional Back Box		86Lx86Wx20H(mm)/86Lx50Wx20H(mm) Stainless steel Panel, 12VDC Waterproof Level IP-68 NO\COM 500000 tested Stainless steel Panel LED Status RED:Standby GREEN:Operation			optional + 
EL-821A/B(LED) Piezoelectric Exit Button Waterproof Level IP- 68		86Lx86Wx20H(mm)/86Lx50Wx20H(mm) Stainless steel Panel, DCV12-24V Waterproof Level IP-68 NO\COM 500000 tested Stainless steel Panel LED Status RED:Standby GREEN:Operation			optional
EL-701S EL-701LS Key switch		With key; Stainless steel panel, wire drawing finished; Defend and Duplicate the Key, Safer to Use; NC/COM, 100,000 tested; 88Lx88Wx20H(mm); optional universal key or unique key			
EL-702EN European type emergency release button with key		EU type with key; Stainless steel panel, wire drawing finished; Reset automatically, open & close (need order); waterproof, Defend and Duplicate the Key, Safer to Use; NO / COM / NC; 100,000 tested; 86Lx86Wx48.5H(mm)			
EL-900A/B/C/D Emergency Break Glass switch (Green/Orange/ RED/white)		Current Rating: 3A@36VDC Max Output Contact: NC\COM Fireproof Material, Easy to install 86Lx86Wx50H(mm), 4 colors optional			
EL-909 Resetable Emergency Release 		Resetable Emergency Release button Current Rating: 3A@36VDC Max Output Contact: NO\NC\COM Fireproof Material, Easy to install 90Lx90Wx56H(mm), 4 colors optional			
AB-902 -12-3/5 Intelligent Access Control Power Supply (12V/3A, 12V/5A)		Intelligent I Power Supply with Space to Put Battery ; 12v, 3/5A ; intelligent, Overcharge and short circuit protection. 226Lx226Wx84H(mm) 110/220VAC+10%;50/60HZ			
PS-901 Power Supply for Access Control		Output Voltage: 12VDC-18VDC; 3A Output Contact: Access control, Electric Lock, Release Button; Time Relay: 0~30sec. Interface inside			

<p>PS-902 -12-3/5 Intelligent Access Control Power Supply (12V/3A, 12V/5A)</p>		<p>Intelligent I Power Supply with Space to Put Battery ; 12v, 3/5A ; LED; intelligent, Overcharge and short circuit protection. 226Lx226Wx84H(mm) 110/220VAC+10%;50/60HZ</p>			
<p>PS-902 -24-3/5 Intelligent Access Control Power Supply (24V/3A, 24V/5A)</p>		<p>Intelligent I Power Supply with Space to Put Battery ; 24v, 3/5A ; LED; intelligent, Overcharge and short circuit protection. 226Lx226Wx84H(mm) 110/220VAC+10%;50/60HZ</p>			
<p>PS904-1203/05 Switch Power Supply for access control, Alarm</p>		<p>Input: 96-260VAC (50/60Hz) Output Voltage: 12VDC/3/5A Contact for Access control, Electric Lock, Release Button</p>			